



INTERSTATE-McBEE

www.interstate-mcbee.com



**Serving the Diesel and
Natural Gas Industry for
over 65 years.**

"Quality without Compromise"



ENGINE KITS FOR THE CUMMINS® ISX MODEL ENGINES

Features and Benefits of the Interstate-McBee Engine Kit:

- Induction hardened cylinder liners for reducing bore wear.
- Forged alloy steel pistons for superior strength.
- Graphite skirt coating on the piston for improved seizure resistance.
- CNC turned piston to precise tolerances.
- Piston pins are hardened and tempered for improved strength and wear resistance.
- Piston rings made from alloy cast iron or steel where required.
- Piston rings are coated on ring faces with wear resistant materials for extended wear characteristics.
- Oil control rings designed with precise tangential tension for proper oil control.
- Tri-metal construction rod and main bearings for durability.
- Multiple steel layer graphite composite head gasket with high temperature seals.
- Head gasket feature a "floating" fire rings to provide complete bore seal.
- OEM gasket materials used throughout for leak free durability.



Our standard engine kit components include:

- Cylinder Kits
- Connecting Rod Bearings
- Main Bearing Set
- Upper Gasket Set
- Lower Gasket Set (O/H only)

Additional items available from Interstate-McBee:

Connecting Rod (Drilled style)	Front & Rear Seal Kits
Connecting Rod Bolts	Exhaust Manifold Bolts
Connecting Rod Bushings	Valve Cover Isolators
Liner Shims	Valve Train Components
Piston Cooling Nozzles	Lube Oil Pump
Camshaft Bushing Set	Oil Cooler Core
Injector O-Ring Kits	Water Pump
Injector Tube Kit	Thermostats
Injector Sleeves	Sensors

©Cummins is a registered trademark of Cummins Inc.

World Headquarters

5300 Lakeside Ave.
Cleveland, OH 44114
PH: 216-881-0015
Fax: 216-881-0805

Florida

9955 NW 58th St.
Doral, FL 33178
PH: 305-863-6650
Fax: 305-863-6272

California

13137 Arctic Circle
Santa Fe Springs, CA 90670
PH: 562-356-5414
Fax: 562-926-2452

Texas

1755 Transcentral Ct. Suite 200
Houston, TX 77032
PH: 281-645-7168
Fax: 281-443-0202